

# SEA CONTAINER SPECIFICATIONS

## DRY CARGO CONTAINERS

### Dimensions



Type	Container Weight			Interior Measurement				Door Open	
	Gross (kg)	Tare (kg)	Net (kg)	Length (m)	Width (m)	Height (m)	Capacity (m³)	Width (m)	Height (m)
20' DC	24,000	2,370	21,630	5.898	2.352	2.394	33.20	2.343	2.280
40' DC	30,480	4,000	26,480	12.031	2.352	2.394	67.74	2.343	2.280

#### CHARACTERISTICS

Manufactured from either Aluminium or steel, they are suitable for most types of cargo / general cargo. Aluminium containers have a slightly larger payload than steel, and steel containers have a slightly larger internal cube.

## HIGH CUBE CONTAINERS

### Dimensions



Type	Container Weight			Interior Measurement				Door Open	
	Gross (kg)	Tare (kg)	Net (kg)	Length (m)	Width (m)	Height (m)	Capacity (m³)	Width (m)	Height (m)
40' HC	30,480	3,980	26,500	12.031	2.352	2.698	76.30	2.340	2.585
45' HC	30,480	4,800	25,680	13.544	2.352	2.698	86.00	2.340	2.585

#### CHARACTERISTICS

With high cube containers, you gain an extra foot in height compared with general-purpose containers. Ideal for light, voluminous cargo or bulky cargo. These extra volume containers come in steel and aluminium.

## REFRIGERATED CONTAINERS

### Dimensions



Type	Container Weight			Interior Measurement				Door Open	
	Gross (kg)	Tare (kg)	Net (kg)	Length (m)	Width (m)	Height (m)	Capacity (m³)	Width (m)	Height (m)
20' RF	24,000	3,050	20,950	5.449	2.290	2.244	26.70	2.276	2.261
40' RF	30,480	4,520	25,960	11.690	2.250	2.247	57.10	2.280	2.205

#### CHARACTERISTICS

Recommended for delicate cargo. Bottom-air delivery system ensures refrigerated cargo reaches its destination in optimum condition.

## OPEN TOP CONTAINERS

### Dimensions



Type	Container Weight			Interior Measurement				Door Open	
	Gross (kg)	Tare (kg)	Net (kg)	Length (m)	Width (m)	Height (m)	Capacity (m³)	Width (m)	Height (m)
20' OT	24,000	2,580	21,420	5.629	2.212	2.311	32.00	2.330	2.263
40' OT	30,480	4,290	26,190	11.763	2.212	2.311	65.40	2.330	2.263

#### CHARACTERISTICS

Allowing cargo to be loaded from the top, open top containers are particularly suitable for bulky cargo such as machinery. They are fitted with a PVC tarpaulin cover and attachable bows with cable sealing devices. The container doors can be removed to make the stuffing of cargo more convenient. Manufactured from steel.

## FLAT RACK CONTAINERS

### Dimensions



Type	Container Weight			Interior Measurement			
	Gross (kg)	Tare (kg)	Net (kg)	Length (m)	Width (m)	Height (m)	Capacity (m³)
20' FR	30,480	2,900	27,580	5.624	2.236	2.234	27.90
40' FR	34,000	5,870	28,130	11.786	2.236	1.968	51.90

#### CHARACTERISTICS

Flatracks are especially suited to heavy loads or cargo that needs loading from the top or sides, such as pipes and machinery. There are collapsible and non-collapsible containers with or without walls. Manufactured from steel.